

**T-2****MINIATURE LAMPS****Applications:****Fuse Style****Dome****Courtesy**

| LINE NO. | DESIGN |       | M.S.C.P. (APPROX.) | LIFE (HRS.) | FILAMENT SHAPE | SF6/6 BASE | BA7S BAYONET BASE | BA7S BAYONET BASE |
|----------|--------|-------|--------------------|-------------|----------------|------------|-------------------|-------------------|
|          | VOLTS  | AMPS  |                    |             |                |            |                   |                   |
| 5        | 6.0    | 0.050 | .060               | 10000       | C-2V           |            | PE 6050S          | PE 6050L          |
| 6        | 6.0    | 0.100 | .180               | 10000       | C-2V           |            | PE 6100S          | PE 6100L          |
| 7        | 6.0    | 0.150 | .350               | 5000        | C-8            | PE 66150-A |                   |                   |
| 8        | 6.0    | 0.200 | .550               | 3000        | C-2R           |            | PE 6200S          | PE 6200L          |
| 9        | 6.3    | 0.150 | .340               | 7000        | C-8            | PE 66315-A |                   |                   |
| 10       | 6.3    | 0.250 | .530               | 10000       | C-8            | PE 66325-A |                   |                   |
| 11       | 6.3    | 0.300 | .600               | 10000       | C-8            | PE 66330-A |                   |                   |
| 12       | 8.0    | 0.200 | .560               | 5000        | C-8            | PE 68200-A |                   |                   |
| 13       | 8.0    | 0.300 | .800               | 5000        | C-8            | PE 68300-A |                   |                   |
| 14       | 12.0   | 0.050 | .137               | 10000       | C-2V           |            | PE 1250S          | PE 1250L          |
| 15       | 12.0   | 0.100 | .315               | 10000       | C-2F           |            | PE 12100S         | PE 12100L         |
| 16       | 12.0   | 0.150 | .600               | 5000        | C-8            | PE 61215-A |                   |                   |
| 17       | 14.0   | 0.100 | .350               | 10000       | C-8            | PE 61410-A |                   |                   |
| 18       | 14.0   | 0.150 | .640               | 5000        | C-8            | PE 61415-A |                   |                   |
| 19       | 24.0   | 0.020 | .105               | 5000        | C-2F           |            | PE 2420S          | PE 2420L          |
| 20       | 24.0   | 0.040 | .220               | 10000       | C-2F           |            | PE 2440S          | PE 2440L          |
| 21       | 24.0   | 0.050 | .300               | 10000       | C-2F           |            | PE 2450S          | PE 2450L          |
| 22       | 24.0   | 0.070 | .500               | 10000       | C-2F           |            | PE 2470S          | PE 2470L          |
| 23       | 24.0   | 0.080 | .500               | 7000        | C-2F           |            | PE 2480S          | PE 2480L          |
| 24       | 30.0   | 0.020 | .130               | 5000        | C-2F           |            | PE 3020S          | PE 3020L          |
| 25       | 30.0   | 0.040 | .250               | 5000        | C-2F           |            | PE 3040S          | PE 3040L          |
| 26       | 30.0   | 0.050 | .340               | 5000        | C-2F           |            | PE 3050S          | PE 3050L          |
| 27       | 36.0   | 0.020 | .150               | 10000       | C-2F           |            | PE 3620S          | PE 3620L          |
| 28       | 48.0   | 0.020 | .200               | 5000        | CC-2F          |            | PE 4820S          | PE 4820L          |
| 29       | 60.0   | 0.020 | .150               | 5000        | CC-2F          |            | PE 6020S          | PE 6020L          |